

4100 CP Nitrogen Membrane Modules



Reliable Nitrogen Membrane Modules are the heart of a nitrogen generation system. **GENERON®** membrane modules have been at the forefront of the industry for over 40 years. Our research and development team in California work to continually improve the performance and durability of our membranes.

By supplying the **GENERON®** membrane modules with compressed air, they generate a nitrogen stream that's suitable for industries including: commercial, food, beverage, laboratory, controlled atmosphere, pharmaceutical, chemical, textile, heat treatment, electronics and many more.

Features & Benefits

Durability by Design

GENERON[®] has been the benchmark of the industry and is proud of the track record of the lowest returnrate while selling >100,000 membranes

Saving Energy

GENERON[®] membrane modules offer the highest efficiency which reduces your compression costs to the minimum

Reducing Footprint

GENERON[®] membrane modules with the highest productivity in the industry allow for the smallest system size and lowest weight

Start-Up is a Breeze

As soon as you supply compressed air to the GEN-ERON[®] membrane modules you will instantaneously produce nitrogen

Reduced CO2 emissions

No heater required to open polymer membrane structure, thus reducing the energy consumption.

Operating Conditions	
Max Pressure	175 PSIG (12.1 barg)
Temperature (Min /Max)	40 °F (4.4 °C) / 131 °F (55 °C)
Max Relative Humidity	80% (no liquid water)
Max Particle Size	0.01 micron

Ease of Installation

GENERON[®] membrane modules allow installation in any available space, whether horizontal or vertical. The large choice of membrane sizes makes the fit easy.

Quality is Guaranteed

Every GENERON[®] membrane module is rigorously QC tested before it leaves our membrane manufacturing facility to ensure it meets the highest flow and purity standards set in our ISO 90001 procedures

Suited for Tough Environments

GENERON[®] membrane modules are built to withstand even the roughest operating conditions, incl. vibrations, pressure– and temperature swings and harsh off-shore or roadside outdoor conditions

Experience Engineering

GENERON[®] membrane modules are designed and built for 10+ years of operation.

Mechanical Description		
Outer Diameter	4.5 inch [114 mm)	
Length	36.5 inch [927 mm]	
Weight	17 lbs [7.7 kg)	
Case Material	6061-T6 Aluminum	

Nitrogen Product Flow Rate at 25°C (77°F) vs. Product Purity						
Pressure	e Nitrogen Product Purity in vol% and Product Flow Rate NCMH (SCFH)			SCFH)		
barg (psig)	95.0%	96.0%	97.0%	98.0%	99.0%	99.5%
6.9	15.9	13.4	11.1	8.8	6.5	5.1
(100)	(614.3)	(517)	(426.2)	(339.8)	(252)	(196.6)
8.5	21	17.6	14.5	11.6	8.6	6.7
(125)	(808)	(679.7)	(559.8)	(446)	(330.2)	(257.1)
10.4	27.1	22.8	18.7	14.9	11	8.6
(150)	(1043.9)	(877.7)	(722.4)	(575)	(425)	(330.4)
12.1	32.5	27.3	22.5	17.9	13.2	10.2
(175)	(1252.7)	(1052.8)	(866.1)	(688.9)	(508.6)	(395)

Air Recovery Rate at 25°C (77°F) [%] vs Product Purity						
Pressure barg (psig)	95.0%	96.0%	97.0%	98.0%	99.0%	99.5%
6.9 (100)	49.5%	45.8%	41.6%	36.8%	30.3%	25.2%
8.5 (125)	50.8%	47.1%	42.9%	38.0%	31.5%	26.4%
10.4 (150)	51.8%	48.1%	43.9%	39.1%	32.6%	27.4%
12.1 (175)	52.4%	48.7%	44.5%	39.7%	33.2%	28.1%

Porting Configuration

Connection	Size
A—Feed	1/2 inch FNPT
B—Product	1/2 inch FNPT
C—Permeate	1 inch FNPT

1. Seal connections with Teflon Tape or Formula 8 Thread Sealant only.

2. Standard Conditions: 77°F (25°C) and 14.696 psi (1 atm)

3. Performance after 1 year (9,000 hours) of continuous operation

4. Recovery = Product N_2 Flow / Feed Flow



GENERON

16250 Tomball Parkway Houston, Texas 77086

713-937-5200 Sales@Generon.com





Go Direct: GENERON Delivers